

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

164.112 Interior Finish (IMO) / Low Flame Spread Surface

HOPEMAN BROTHERS, INC 435 ESSEX AVE WAYNESBORO VA 22980

164.112/0002/0	APPROVED	Type 604 plastic laminate approved in a nominal thickness of 0.028 inches	(0.7 mm).
164.112/0003/0	APPROVED	Type 607 plastic laminate approved in a nominal thickness of 0.062 inches	(1.6 mm).
164.112/0008/0	APPROVED	Type 604 plastic laminate approved in a nominal thickness of 0.028 inches	(0.7 m m).

INTERNATIONAL PAPER DECORATIVE PRODUCTS DIV. HAMPTON SC 29924

164.112/0004/0	APPROVED	Micarta Type MFR Laminate (MD-28607), approved in nominal thickness of	0.026 to 0.036 inches (0.6 to 0.
----------------	----------	--	----------------------------------

KELLER-NOVOPAN AG INDUSTRIESTRASSE 7 CH 5314 KLEINDOTTINGEN

164.112/0007/0	APPROVED	Type "Kellco" high pressure plastic laminate, approved in nominal thickness	of 0.8 mm and 1.0 mm.
----------------	----------	---	-----------------------

WILSONART INTERNATIONAL, INC. 505 SOUTH GENERAL BRUCE DRIVE P. O. BOX 6110 TEMPLE TX 76503

164.112/0005/0	APPROVED	Type 335 Decorative Laminate approved in nominal thickness of 0.028 inches	(0.7 mm).
164.112/0006/0	APPROVED	Type 203 Backer Laminate approved in nominal thickness of 0.030 inches	(0.75 mm).
164.112/0132/0	APPROVED	Type 203 Backer laminate approved in a nominal thickness of 0.030 inches	(0.7 mm).

164.207 Fire-Resisting Divisions for High Speed Craft

THERMAL CERAMICS 2102 OLD SAVANNAH ROAD P. O. BOX 923 AUGUSTA GA 30903

164.207/0001/0	APPROVED	"FireMaster Marine Blanket", Calcium Magnesium-Silicate fiber insulation,	96 kg/cu.m. density.
----------------	----------	---	----------------------